
Chemicals & sprayers

Foamjet



Continuous pneumatic foam sprayers need a permanent connection to an air compressor; in this way air mixes with the chemical product producing a soft and voluminous foam that persists on surfaces: with a little chemical product, it is possible to treat wider areas or tough dirt (also on ceilings, inclined and/or slippery walls). They work at high-pressure and so they use capacious steel or stainless steel tanks to allow a greater working autonomy.

Standard accessories: • Professional gun. • Lance with nozzle. • Integrated inlet and outlet quick. • Chemical use hose and gasket. Foamjet 24 600 mm |← code 0.906.0035 10 m code 0.906.0084 Foamjet 50 900 m ---code 0.906.0036 code 0.906.0084



	FOAMJET SV24	FOAMJET SX24	FOAMJET SV50	FOAMJET SX50
code	0.006.0007	0.006.0009	0.006.0008	0.006.0010
capacity/model	24 l/painted	24 I/S/S	50 l/painted	50 I/S/S
working pressure	6 bar	6 bar	6 bar	6 bar
safety valve	max 8 bar	max 8 bar	max 8 bar	max 8 bar
pressure indicator	pressure gauge	pressure gauge	pressure gauge	pressure gauge
level indicator	external column	external column	external column	external column
recharging	air operating	air operating	air operating	air operating
pressure regulator	manual	manual	manual	manual
gun connection	1/4" G-F	1/4" G-F	1/4" G-F	1/4" G-F
hose type	rilsan	rilsan	rilsan	rilsan
hose / lance lenght	10 mt / 600 mm	10 mt / 600 mm	10 mt / 900 mm	10 mt / 900 mm
dimension / weight	28x32x75 cm / 15 kg - 33,06 lbs	28x32x75 cm / 11 kg - 24,25 lbs	45x42x100 cm / 25 kg - 55,11 lbs	45x42x102 cm / 18 kg - 39,68 lbs